



FireNEX-5000™
(Upstream)




FireNEX-5000™ (Downstream)

Main Features

- USB 3.0 signals up to 100+ meters
- Standard optical port (LC connector)
- Two Standard USB 3.0 A ports (Upstream unit)
- One Standard USB 3.0 A port and One Standard USB 3.0 B port (Downstream unit)
- Works with PCs, Macs and Linux
- Light Weight: 173 g
- Compact size: 79 x 69 x 31 mm
- Data rate: 5000 Mbps
- Plug and Play
- ROHS Compliant
- FCC and CE Compliant
- Industrial standard screw locking for all USB ports

Innovative Design



Technical Specification

Range	
Length	up to 100+ meters
Data Transfer Speed	
USB 3.0	5 Gbps/5000 Mbps
Properties	
CONNECTORS	
Upstream (Device)	2 standard USB 3.0 A ports
Downstream (PC)	1 standard USB 3.0 A port and 1 standard USB 3.0 B port
Optical	LC connector (standard optical port)
SIZE	
Enclosure Dimensions	79 x 69 x 31 mm
Weight	173 g
Power	
Source (Downstream)	Bus Power
Source (Upstream)	External, supplied with the included FireNEX-5V Power Adaptor
Compliance	
RoHS	Compliant
EMC	Compliant
FCC	Compliant
CE	Compliant
Support	
Manufacturer Warranty	1 year

Application

- Machine Vision Camera Connections
- Other computer or controller to device connections
- External Storage Connections




FireNEX-5000™

PRODUCT DATA SERIES

3041 Olcott St. | Santa Clara, CA 95054, USA
+1.408.986.8024 | f +1.408.986.9988 | p
information@newnex.com | e www.newnex.com | w

Breaking the Length Barrier




Although based on the USB-IF Compliance for A to micro B connection, the recommended practical length limit for USB 3.0 is one meter, as the world's first USB 3.0 Optical Repeater, FireNEX-5000™ is capable of extending full-speed USB 3.0 signals of 5.0 Gbps at over 100 times the recommended length, extending up to 100+ meters in distance. This increases application versatility, especially for devices that need to be mounted at a distance away from the controller.

Durable

The FireNEX-5000™ features small metal enclosures which are durable and have better EMI shielding.

Light and Compact

Weighing at 173 grams and 79 x 69 x 31mm dimensions (about the size of a standard computer mouse), The FireNEX-5000™ provides connectivity without taking up space in your busy workstation.



Super Speed USB 3.0

The FireNEX-5000™ provides FULL USB 3.0 Signal transfer at up to 5.0 Gbps.



Low Power Consumption

FireNEX-5000™ consumes significantly low power that the PC side is completely BUS Powered and the Device side only needs additional 5V.

User Friendly

The FireNEX-5000™ implements the true plug-and-play features compatible with PCs, Macs, and Linux with no additional drivers.

Machine Vision Compliant

Ensuring reliable connection for Machine Vision Application, The FireNEX-5000™ comes with Machine Vision Compliant Screw Hole Spacing.



RoHS Compliant

The FireNEX-5000™ follows the guidelines for restricted dangerous substances in its manufacturing, containing less than 0.01% of Lead (Pb), Cadmium (Cd) and Mercury (Hg).

Contact Us

For any further questions, please contact us at:

3041 Olcott St.
Santa Clara, CA 95054
USA

- email. information@newnex.com
- phone. +1-408-986-9988
- fax. +1-408-986-8024
- website. www.newnex.com