


THIS DOCUMENT AND THE DATA DISCLOSED HEREIN
OR WITHIN IS NOT TO BE REPRODUCED, USED, OR
DISCLOSED IN WHOLE OR PART TO ANYONE WITHOUT
THE WRITTEN PERMISSION OF NEWNEX



Wiring Structure			
USB 3.2 A Plug	Wire		USB Typ-C Plug
	SIGNAL	COLOR	
1	Vcc	Red	A4,B4,A9,B9
-	CC		A5
2	UTP-Dn	White	A7
3	UTP-Dp	Green	A6
4+7	GND	Black+D	A1,B1,A12,B12
5	SDPn1	Blue	A3
6	SDPp1	Yellow	A2
8	SDPn2	Purple	B10
9	SDPp2	Orange	B11
SHELL	Outer Braid		SHELL

 $R_p = 56K$

1. Cable: USB 3.2 High Flex Cables, 6.3mm O.D, Orange Jacket.
2. Connector: USB A Male
3. Connector: USB Angled Type-C Male Dual Screw Locking.
4. Recommended Min Bending Radius: 12 x O.D
5. Max Drag Chain Travel Distance: 1 meter
6. Rated Flex Life Cycle: 6,000,000
7. Packaging: 1 Piece + PE bag.

Newnex Technology Corp. 			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE:		PROJ: 	
FRACS: DECIMALS ANGLES $\pm$ NA $\pm$ 0.5 $\pm$ 0.5° $\pm$ NA $\pm$ 0.25 $\pm$ 0.125		SCALE: 1:1 REV. A	
DATE: 12/26/2024		TITLE: High Flex USB 3.2 Cable, A Male to Angled Type C Male with Dual Screw Locking, 1m, Orange.	
PART NUMBER: U3HLA01C6D-010		DRAWN BY: XW APPROVED BY:	
REVISION COMMENTS:		CHECKED BY:	
Drawings generated		SHEET 1 OF 1	