

NEWNEX PROPRIETARY


THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WITHIN IS NOT TO BE REPRODUCED, USED, OR DISCLOSED IN WHOLE OR PART TO ANYONE WITHOUT THE WRITTEN PERMISSION OF NEWNEX

COMPANY NAME

CUSTOMER SIGNATURE

DATE

COMMENTS:



WIRING STRUCTURE

A	SIGNAL	MicroB
1	PWR	1
2	D-	2
3	D+	3
4	GND	5
5	SDP1-	6
6	SDP1+	7
7	DRAIN	8
8	SDP2-	9
9	SDP2+	10
SHELL	BRAID	SHELL

Notes:

1. Cable: USB 3.2 Black PVC Jacket.
2. Connector: USB 3.2 Angled Micro B Male Locking.
3. Connector: USB 3.2 A Male.
4. Packaging: 1 Piece + PE bag.

Newnex Technology Corp.



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE:

FRACTIONS DECIMALS ANGLES
 # NA XX ± 0.5 ± 0.5
 .XX ± 0.25 ± 0.5
 .XXX ± 0.125 ± 0.5

PROJ: [Symbol] TITLE: USB 3.2 Angled Micro B Male Locking to A Male, Black.

SCALE: 1:1 REV: A

DATE: 4/9/2026

DRAWN BY: XW

APPROVED BY:

PART NUMBER: US2-AMCBR2I-XX

CHECKED BY:

SHEET 1 OF 1

REVISION COMMENTS: Drawing generated

*100% OPEN, SHORT, MISWIRE TESTING;
 *RoHS COMPLIANT PRODUCT;
 *BOTH SHELL CLAM AND COPPER FOIL HAVE 360 DEGREE CONTACT WITH BRAIDING;